



GY Series

35 Volts • CE • XT-35D Controller 

0,7 to 9,8 NM

- Excellent ratio Weight / Ergonomy / Power
- BLDC motor (maintenance free)
- High speed from 300 to 1500 rpm (3 models)
- Designed for high production rate
- Motor efficiency 85%
- Low Noise, Low Heat, less Energy consumption
- Over Heat, Over Load, Over Voltage protection circuit with LED display
- ESD free with conductive plastic body (less than 10000 hms)
- Noise level : <70 dBA, vibration level : <2,5 m/s²



Model	Torque Range (Nm)	Speed Rotation (rpm)	Starting system	Drive	Weight (Kg)	Code
GY35 ESD-G	0,7 - 3,4	500 to 1500	Lever	Hex 1/4"	0,8	6-1064100
GY50 ESD-G	1 - 4,9	400 to 1100	Lever	Hex 1/4"	0,8	6-1064102
GY100 ESD-G	3,9 - 9,8	250 to 500	Lever	Hex 1/4"	0,85	6-1064104
GY35P ESD-G	0,7 - 3,4	500 to 1500	Push to start	Hex 1/4"	0,8	6-1064101
GY50P ESD-G	1 - 4,9	400 to 1100	Push to start	Hex 1/4"	0,8	6-1064103
GYA35 ESD-G V2	0,7 - 3,4	500 to 1500	Remote	Hex 1/4"	0,95	6-1064105
GYA50 ESD-G V2	1 - 4,9	400 to 1100	Remote	Hex 1/4"	0,95	6-1064106
GYA100 ESD-G V2	3,9 - 9,8	250 to 500	Remote	Hex 1/4"	0,95	6-1064107
PGY35 pistol ESD-G	0,7 - 3,4	500 to 1500	Trigger	Hex 1/4"	0,9	6-1078015
PGY50 pistol ESD-G	1 - 4,9	400 to 1100	Trigger	Hex 1/4"	0,9	6-1078016
PGY100 pistol ESD-G	3,9 - 9,8	250 to 500	Trigger	Hex 1/4"	0,95	6-1078017
PGY35 T pistol Top Exit ESD-G	0,7 - 3,4	500 to 1500	Trigger	Hex 1/4"	0,9	6-1078018
PGY50 T pistol Top Exit ESD-G	1 - 4,9	400 to 1100	Trigger	Hex 1/4"	0,9	6-1078019
PGY100 T pistol Top Exit ESD-G	3,9 - 9,8	250 to 500	Trigger	Hex 1/4"	0,95	6-1078020

* The whole models of this series are delivered with one tool cable (3m) + sample powerbits.